

SOLAR ENERGY DICTIONARY

A

Absorber — the material in a photovoltaic device that readily absorbs solar radiation through a heat-transfer fluid (usually water + antifreeze). This liquid is then heated and circulated between the collector and storage tank. Absorption at higher frequencies is can be accomplished through the use of black absorbers, or even higher with selective coatings.

AC — alternating current, a type of electrical current which reverses direction [or polarity] is at regular intervals or cycles. In the USA, the standard is 120 reversals or 60 cycles per second [commonly referred to as 60 Hertz]. Many other countries use 50 Hertz as a standard. Electricity transmission networks use AC because voltage can be controlled easily.

AC Side Isolation Switch — is used to make sure that an electrical circuit can be completely de-energized for service or maintenance. Such switches are often found in industrial applications where machinery must have its source of driving power removed for adjustment or repair. The switch allows isolation of devices such as circuit breakers, transformers or transmission lines for maintenance.

Activated Shelf Life — the period of time that a charged battery can be stored at a specified temperature before its capacity falls to an unusable level.

Activation Voltage(s) — The voltage(s) at which a charge controller will take action to protect the batteries.

Active Solar — is the conversion of solar energy directly into functional light or heat by using mechanical or electrical equipment such as fans and pumps. Both the solar heat and solar electricity can be stored and transported.

Adjustable Set Point — a feature allowing the user to adjust the voltage levels at which a charge controller will become active.

Alternating Current (AC) — A type of electrical current, the direction of which is reversed at regular intervals or cycles. See AC for more information.

Acceptor — A dopant material, such as boron, that has fewer outer shell electrons than required in an otherwise balanced crystal structure. This provides a hole that can accept a free electron.

AGM — Absorbed Glass Mat - a sealed battery that uses saturated absorbed glass mats rather than a gelled or liquid electrolyte between the plates. AGM batteries are more expensive than gel cell batteries or flooded types but have superior performance.

AH/Ah — abbreviation of ampere-hour

AIC — Amperage Interrupt Capability - direct current fuses should be rated with a sufficient AIC to interrupt the highest possible current.

Air mass (also called air mass ratio) — equal to the cosine of the zenith angle -that angle from directly overhead to a line intersecting the sun. The air mass is an indication of the length of the path solar radiation travels through the atmosphere. An air mass of 1.0 means the sun is directly overhead and the radiation travels through one atmosphere (thickness).

Alternative Energy — an accepted term for "non-conventional" energy systems usually on a smaller scale. Alternative energy includes solar electric systems, wind generator systems, and small hydro-electric systems.

Alternator — A generator producing AC (alternating current) rather than DC (direct current). Alternators are more efficient than DC generators and in automobiles the alternator output is converted to 12 volts DC using rectifier diodes built into the alternator.

Ambient Temperature — the temperature of the surrounding area.

Amorphous Semiconductor — a non-crystalline semiconductor material that has no long-range order.

Amorphous Silicon — a thin-film, silicon photovoltaics cell having no crystalline structure. This type of cell is manufactured by depositing layers of doped silicon on a substrate.

Amperage Interrupt Capability (AIC) — direct current fuses should be rated with a sufficient AIC to interrupt the highest possible current.

Ampere (amp) — a unit of electrical current or rate of flow of electrons. One volt across one ohm of resistance causes a current flow of one ampere.

Ampere-Hour (Ah/AH) — a measure of the flow of current (in amperes) over one hour; used to measure battery capacity.

Ampere Hour Meter — an instrument that monitors current with time. The indication is the product of current (in amperes) and time (in hours).

Angle of Incidence — the angle at which direct sunlight strikes the surface of the solar panel relative to perpendicular. Sunlight with an incident angle of 90 degrees is the most efficient. A surface that directly faces the sun has a solar angle of incidence of zero, but if the surface is parallel to the sun (for example, sunrise striking a horizontal rooftop), the angle of incidence is 90°.

Angle of Inclination — the angle that a solar array is positioned above horizontal – with 90 degrees being vertical. A general rule of thumb is to set the angle of a solar array to the latitude +/- 15 degrees.

Annual Solar Savings — the annual solar savings of a solar building is the energy savings attributable to a solar feature compared to the energy requirements of a non-solar building.

Anode — the positive electrode in an electrochemical cell (or battery). Also, the earth or ground in a cathodic protection system. It is also the positive terminal of a diode.

Antireflection Coating — a thin coating of a material applied to a solar cell surface that reduces the light reflection on its surface and increases light transmission.

AEER — (Appliance Energy Efficiency Ratings) Operating efficiency of appliances as set by the U.S. Department of Energy guidelines.

Array — any number of solar photovoltaic modules or panels connected together to provide a single electrical output.

Array Current — the electrical current produced by a photovoltaic array when it is exposed to sunlight.

Array Operating Voltage — the voltage produced by a photovoltaic array when exposed to sunlight and connected to a load.

Asynchronous Generator — an electric generator that produces alternating current that matches an existing power source.

Autonomous System — a stand-alone power system that has no utility connection. Most autonomous systems are designed for 3-5 days of power from batteries without recharging from a solar source or standby generator. Also called a stand-alone system.

Availability — the quality or condition of a photovoltaic system being available to provide power to a load. This is usually measured in hours per year. One minus availability equals downtime.

Azimuth Angle — the angle between true south and the point on the horizon directly below the sun.

B

Balance of System — represents all components and costs other than the photovoltaic modules/array. It includes design costs, land, site preparation, system installation, support structures, power conditioning, operation & maintenance costs, indirect storage, related costs.

Band Gap — in a semiconductor, the energy difference between the highest valence band and the lowest conduction band.

Band Gap Energy (Eg) — the amount of energy (in electron volts) required to free an outer shell electron from its orbit about the nucleus to a free state, and thus promote it from the valence to the conduction level.

Barrier Energy — the energy given up by an electron in penetrating the cell barrier; a measure of the electrostatic potential of the barrier.

Base Load — the average amount of electric power that a utility must supply in any period.

Batch System — a type of passive solar water heating which uses a "batch" heater, to store household water in a series of metal tubes enclosed in glass tubes. The sun shines on the tubes and warms the water inside. It does not require an auxiliary source of power, pumps or electronic controls to deliver solar heated water to your faucet.

Battery — a device containing electrolytic cells to store electrical energy in chemical form. Two or more electrochemical cells enclosed in a container and electrically interconnected in an appropriate series/parallel arrangement to provide the required operating voltage and current levels. It also applies to a single cell if it constitutes the entire electrochemical storage system.

Battery Available Capacity — the total maximum charge that can be withdrawn from a cell or battery under a specific set of operating conditions such as discharge rate, temperature, initial state of charge, age, and cut-off voltage. It is normally expressed in ampere-hours.

Battery Capacity — the maximum total electrical charge, expressed in ampere-hours, which a battery can deliver to a load under a specific set of conditions.

Battery Cell — the simplest operating unit in a storage battery. It consists of one or more positive electrodes or plates, an electrolyte that permits ionic conduction, one or more negative electrodes or plates, separators between plates of opposite polarity, and a container for all the above. A lead acid cell produces about 2.12 volts and a 12-volt battery uses six of these cells and fully charged measures about 12.72 volts.

Battery Cycle Life — the number of cycles, to a specified depth of discharge, that a cell or battery can undergo before failing to meet its specified capacity or efficiency performance criteria.

Battery Energy Capacity — the total energy available [or total number of ampere-hours [Ah] that a fully-charged battery can output. The energy capacity of a given cell varies with temperature, rate, age, and cut-off voltage.

Battery Energy Storage — energy storage using electrochemical batteries. The three main applications for battery energy storage systems include spinning reserve at generating stations, load leveling at substations, and peak shaving on the customer side of the meter.

Battery Life — the period during which a cell or battery is capable of operating above a specified capacity or efficiency performance level. Life may be measured in cycles and/or years, depending on the type of service for which the cell or battery is intended.

BIPV (Building-Integrated Photovoltaics) — the design and integration of photovoltaic (PV) technology into the building envelope, typically replacing conventional building materials. This integration may be in vertical facades, replacing view glass, spandrel glass, or other facade material; into semitransparent skylight systems; into roofing systems, replacing traditional roofing materials; into shading "eyebrows" over windows; or other building envelope systems.

Blocking Diode — a semiconductor connected in series with a solar cell or cells and a storage battery to keep the battery from discharging through the cell when there is no output, or low output, from the solar cell. The blocking diode is like a one-way valve that allows electrons to flow forwards, but not backwards.

Buffer Storage — is temporary storage that makes the supply of solar energy feasible independent of weather conditions, time of year or the time of day. Batteries are used for this purpose in photovoltaic systems. In solar heating systems the heat can be stored for short periods of time in a water storage tank or for longer periods in a long-term hot water storage tank.

Boron (B) — a chemical element commonly used as the dopant in photovoltaic device or cell material.

Boule — a sausage-shaped, synthetic single-crystal mass grown in a special furnace, pulled and turned at a rate necessary to maintain the single-crystal structure during growth. Solar cells are made from silicon boules, polycrystalline structures that have the atomic structure of a single crystal. The most commonly used process for creating the boule is called the Czochralski method.

Btu (British Thermal Unit) — the amount of heat required to raise the temperature of one pound of water one degree Fahrenheit; equal to 252 calories.

Bus (electrical) — an electrical conductor that serves as a common connection point for multiple connections.

Bypass Diode — a diode connected across one or more solar cells in a photovoltaic module such that the diode will conduct if the cell(s) become reverse biased. It protects these solar cells from thermal destruction in case of total or partial shading of individual solar cells while other cells are exposed to full light.

C

Cadmium (Cd) — a chemical element used in making certain types of solar cells and batteries.

Cadmium Telluride (CdTe) — a polycrystalline thin-film photovoltaic material.

Capacity (C) — same as battery capacity - the maximum total electrical charge, expressed in ampere-hours, which a battery can deliver to a load under a specific set of conditions.

Capacity Factor — the ratio of the average load on (or power output of) an electricity generating unit or system to the capacity rating of the unit or system over a specified period of time.

Captive Electrolyte Battery — a battery having an immobilized electrolyte (gelled or absorbed in a material).

Cathode — the negative pole or electrode of an electrolytic cell, vacuum tube, etc., where electrons enter (current leaves) the system; the opposite of an anode.

Cathodic Protection — a method of preventing oxidation of the exposed metal in structures by imposing a small electrical voltage between the structure and the ground.

Cd — the chemical element symbol for cadmium

CdTe — the chemical element symbol for cadmium telluride

Cell (battery) — a single unit of an electrochemical device capable of producing direct voltage by converting chemical energy into electrical energy. A battery usually consists of several cells electrically connected together to produce higher voltages. The terms cell and battery are sometimes used interchangeably.

Cell Barrier — a very thin region of static electric charge along the interface of the positive and negative layers in a photovoltaic cell. The barrier inhibits the movement of electrons from one layer to the other, so that higher-energy electrons from one side diffuse preferentially through it in one direction, creating a current and thus a voltage across the cell. This can also be called depletion zone or space charge.

Cell Junction — the area of immediate contact between two layers (positive and negative) of a photovoltaic cell. The junction lies at the center of the cell barrier or depletion zone.

Charge — the process of adding electrical energy to a battery.

Charge Carrier — a free and mobile conduction electron or hole in a semiconductor.

Charge Controller — a component of a photovoltaic system that controls the flow of current to and from the battery to protect it from over-charge and over-discharge. The charge controller may also indicate the system operational status.

Charge Factor — the time in hours during which a battery can be charged at a constant current without damage to the battery. This is usually expressed in relation to the total battery capacity. For example, C/5 indicates a charge factor of 5 hours.

Charge Rate — the current applied to a cell or battery to restore its available capacity. This rate is commonly normalized by a charge control device with respect to the rated capacity of the cell or battery.

Charge Regulator — a device used to control and monitor the charging and discharging of batteries. The function of the charge regulator is to prevent the overcharging or discharging of the battery. The charging voltage is also optimally matched to the battery's charge condition.

Chemical Vapor Deposition (CVD) — a method for bonding thin semiconductor films used to make certain types of photovoltaic devices. With the CVD method, a substrate is exposed to one or more vaporized compounds, one or more of which contain desirable constituents. A chemical reaction is initiated, at or near the substrate surface, to produce the desired material that will condense on the substrate.

CIS — abbreviation for copper indium diselenide, a chemical used for the selective coating of Solar Cells. CIS thin film solar cells consist of multiple layers of CuInSe₂ with varying amounts of contaminating elements

Cleavage of Lateral Epitaxial Films for Transfer (CLEFT) — a process for making inexpensive Gallium Arsenide (GaAs) photovoltaic cells in which a thin film of GaAs is grown atop a thick, single-crystal GaAs (or other suitable material) substrate and then is cleaved from the substrate and incorporated into a cell, allowing the substrate to be reused to grow more thin-film GaAs.

Cloud Enhancement — the increase in solar intensity caused by reflected irradiance from nearby clouds.

Collector Glazing — a part of a solar collector that is transparent to solar radiation. It reduces heat loss and protects the absorber from the elements. In order to reach high temperatures and reduce losses in a collector, the glazing is often made of multiple layers (double-paned glass) or honeycomb layers.

Combiner Box — a solar array junction box where multiple solar modules are electrically connected together and fusing devices may be located.

Combined Collector — a photovoltaic device or module that provides useful heat energy in addition to electricity.

Concentrating Solar Power (CSP) — the technique of concentrating sunlight by using mirrors to create heat. The heat is then used to raise steam and drive turbines and generators, just like a conventional power station. It is possible to store solar heat in melted salts so that electricity generation may continue through the night or on cloudy days

Concentrator — a photovoltaic module, which includes optical components such as lenses to direct and concentrate sunlight onto a solar cell of smaller area. Most concentrator arrays must directly face or track the sun. They can increase the power flux of sunlight hundreds of times.

Conduction Band (or conduction level) — an energy band in a semiconductor in which electrons can move freely in a solid, producing a net transport of charge.

Conductor — the material through which electricity is transmitted, such as an electrical wire, or transmission or distribution line.

Contact Resistance — the resistance between metallic contacts and the semiconductor.

Conversion — the transformation of energy, i.e. light, into heat (solar heating) or electrical power (photovoltaics).

Conversion Efficiency — the ratio of the electric power produced by a photovoltaic device to the power of the sunlight incident on the device. Solar panels are normally 9% to 14% efficient. Same as photovoltaic (conversion) efficiency.

Converter — a unit that converts a direct current (dc) voltage to another dc voltage.

Copper Indium Diselenide (CuInSe₂, or CIS) — a polycrystalline thin-film photovoltaic material (sometimes incorporating gallium (CIGS) and/or sulfur).

Crystalline Silicon — a type of photovoltaic cell made from either a slice of single-crystal silicon or a polycrystalline silicon.

Current — same as electric current; the flow of electrical energy – or electricity - in a conductor and measured in amperes.

Current at Maximum Power (I_{mp}) — the current at which maximum power is available from a module.

Cutoff Voltage — the voltage levels at which the charge controller disconnects the photovoltaic array from the battery or the load from the battery.

Cycle — the discharge and then subsequent charge of a battery.

Czochralski Process — a method of growing large size, high quality semiconductor crystal by slowly lifting a seed crystal from a molten bath of the material under careful cooling conditions.

D

Dangling Bonds — a chemical bond associated with an atom on the surface layer of a crystal. The bond does not join with another atom of the crystal, but extends in the direction of exterior of the surface.

Days of Storage — The number of consecutive days the stand-alone system will meet a defined load without solar energy input. This term is related to system availability.

DC — a type of electricity transmission and distribution by which electricity flows in one direction through the conductor, usually relatively low voltage and high current. See direct current for more info.

DC Side Isolation Switch — is used to make sure that an electrical circuit can be completely de-energized for service or maintenance. Such switches are often found in applications where machinery must have its source of driving power removed for adjustment or repair. The isolating switch is necessary to turn power off photovoltaic [PV] systems under load. Without this type of switch there is a real time risk of electrical shock.

DC-to-DC Converter — an electronic circuit to convert direct current voltages (e.g., photovoltaic module voltage) into other levels (e.g., load voltage). This can be part of a maximum power point tracker.

Deep-Cycle Battery — a battery with large plates that can withstand many discharges to a low state-of-charge.

Deep Discharge — the discharging of a battery to 20% or less of its full charge capacity.

Depth of Discharge (DOD) — the ampere-hours removed from a fully charged cell or battery, expressed as a percentage of rated capacity. For example, the removal of 25 ampere-hours from a fully charged 100 ampere-hours rated cell results in a 25% depth of discharge. Under certain conditions, such as discharge rates lower than that used to rate the cell, depth of discharge can exceed 100%.

Dendrite — a slender threadlike spike of pure crystalline material, such as silicon.

Dendritic Web Technique — a method for making sheets of polycrystalline silicon in which silicon dendrites are slowly withdrawn from a melt of silicon whereupon a web of silicon forms between the dendrites and solidifies as it rises from the melt and cools.

Depletion Zone — same as the cell barrier. The term is derived from the fact that this microscopically-thin region is depleted of charge carriers (free electrons and hole).

Design Month — the month having the combination of insolation and load that requires the maximum energy from the photovoltaic array.

Diffuse Insolation — sunlight received indirectly as a result of scattering due to clouds, fog, haze, dust, or other obstructions in the atmosphere. Diffuse Insolation is the opposite of direct insolation.

Diffuse Radiation — unfocused sunlight scattered by atmospheric particles and arriving at the earth's surface from all directions.

Diffusion Furnace — a type of furnace used to make junctions in semiconductors by diffusing dopant atoms into the surface of the material.

Diffusion Length — the mean distance a free electron or hole moves before recombining with another hole or electron.

Diode — an electronic device that allows current to flow in one direction only. Two types of diodes are a blocking diode or a bypass diode.

Direct Beam Radiation — radiation received by direct solar rays. It is measured by a pyrheliometer with a solar aperture of 5.7° to transcribe the solar disc.

Direct Current (DC) — a type of electricity transmission and distribution by which electricity flows in one direction through the conductor, usually relatively low voltage and high current. To be used for typical 120-volt or 220-volt household appliances, DC must be converted to alternating current [AC], its opposite.

Direct Insolation — sunlight falling directly upon a collector. Direct Insolation is the opposite of diffuse insolation.

Discharge — the withdrawal of electrical energy from a battery.

Discharge Factor — a number equivalent to the time in hours during which a battery is discharged at constant current usually expressed as a percentage of the total battery capacity, i.e., C/5 indicates a discharge factor of 5 hours.

Discharge Rate — the rate, usually expressed in amperes or time, at which electrical current is taken from the battery.

Disconnect — switch gear used to connect or disconnect components in a photovoltaic system.

Distributed Energy Resources (DER) — a variety of small, modular power-generating technologies that can be combined with energy management and storage systems. They are used to improve the function of the electricity delivery system, whether or not those technologies are connected to an electricity grid.

Distributed Generation — a popular term for localized or on-site power generation.

Distributed Power — a generic term for any power supply located near the point where the power is used. Distributed power is the opposite of central power.

Distributed Systems — systems that are installed at or near the location where the electricity is used, as opposed to central systems that supply electricity to grids. A residential photovoltaic system is a distributed system.

Donor — in a photovoltaic device, an n-type dopant, such as phosphorus, that puts an additional electron into an energy level very near the conduction band; this electron is easily excited into the conduction band where it increases the electrical conductivity over than of an undoped semiconductor.

Donor Level — the level that donates conduction electrons to the system.

Dopant — a chemical element (or impurity) added in small amounts to an otherwise pure semiconductor material to modify the electrical properties of the material. A n-dopant introduces more electrons. A p-dopant creates electron holes or vacancies.

Doping — the act of adding dopants to a semiconductor.

Downtime — the time period when the photovoltaic system cannot provide power for the load. This is usually expressed in hours per year or that percentage.

Drainback System — or DBS, provides for the automatic emptying of the Collector and piping whenever the system is turned off or whenever the collector temperature strays outside a specified temperature range. The circulation pump shuts itself down and then the water drains by gravity to the storage tank and Heat Exchanger. By means of such drainback systems the overheating or freezing of a solar heating system can be avoided.

Dry Cell — a cell (or battery) with a captive electrolyte. It is primary battery that cannot be recharged.

Duty Cycle — the ratio of active time to total time. Used to describe the operating regime of appliances or loads in photovoltaic systems.

Duty Rating — the amount of time an inverter (power conditioning unit) can produce at full rated power.

E

Edge-Defined Film-Fed Growth (EFG) — a method for making sheets of polycrystalline silicon for photovoltaic devices in which molten silicon is drawn upward by capillary action through a mold.

Electric Circuit — the path followed by electrons from a power source – such as a generator or battery - through an electrical system, and returning to the source.

Electric Current — the flow of electrical energy (electricity) in a conductor, measured in amperes.

Electrical grid — a large integrated system of electricity distribution from centralized locations to individual homes and businesses

Electricity — electrical energy resulting from the flow of charged particles, such as electrons or ions.

Electrochemical Cell — a device containing two conducting electrodes, one positive and the other negative, made of dissimilar materials (usually metals) that are immersed in a chemical solution (electrolyte) that transmits positive ions from the negative to the positive electrode and thus forms an electrical charge. One or more cells constitute a battery.

Electrode — a conductor that is brought in conducting contact with a ground.

Electrodeposition — electrolytic process in which a metal is deposited at the cathode from a solution of its ions.

Electrolyte — a nonmetallic (liquid or solid) conductor that carries current by the movement of ions (instead of electrons) with the liberation of matter at the electrodes of an electrochemical cell.

Electromagnetic Energy — energy that is generated from an electromagnetic field produced by a magnet or an electric current flowing through a conductor.

Electromagnetic Field (EMF) — the electrical and magnetic fields produced by any device operating with electricity.

Electron — an elementary particle of an atom with a negative electrical charge and a mass of 1/1837 of a proton; electrons surround the positively charged nucleus of an atom and determine the chemical properties of an atom. The movement of electrons in an electrical conductor constitutes an electric current.

Electron Volt (eV) — the amount of kinetic energy gained by an electron when accelerated through an electric potential difference of 1 Volt; equivalent to 1.603×10^{-19} ; a unit of energy or work.

Energy — the capability of doing work; different forms of energy can be converted to other forms, but the total amount of energy remains the same.

Energy Audit — a survey that shows how much energy used in a home and helps find ways to use less energy.

Energy Contribution Potential — recombination occurring in the emitter region of a photovoltaic cell.

Energy Density — the ratio of available energy per pound; usually used to compare storage batteries.

Energy Levels — the energy represented by an electron in the band model of a substance.

Energy Payback Period — The time span that a solar energy system requires to produce as much energy as was needed for production of the system.

Epitaxial Growth — the growth of one crystal on the surface of another crystal. The growth of the deposited crystal is oriented by the lattice structure of the original crystal.

Equalization — the process of restoring all cells in a battery to an equal state-of-charge. Some battery types may require a complete discharge as a part of the equalization process.

Equalization Charge — the process of mixing the electrolyte in batteries by periodically overcharging the batteries for a short time.

Equalizing Charge — a continuation of normal battery charging, at a voltage level slightly higher than the normal end-of-charge voltage, in order to provide cell equalization within a battery.

Equinox — the two times of the year when the sun crosses the equator and night and day are of equal length; usually occurs on March 21st (spring equinox) and September 23 (fall equinox).

Evacuated Tube Collector – a type of solar collector in which the absorber is inside an air-evacuated glass tube allowing energy loss to be further reduced and temperatures up to 150 °C (302 °F) can be reached. Additionally, evacuated-tube collectors also work on slightly cloudy days.

Extrinsic Semiconductor — the product of doping a pure semiconductor.

F

Fermi Level — energy level at which the probability of finding an electron is one-half. In a metal, the Fermi level is very close to the top of the filled levels in the partially filled valence band. In a semiconductor, the Fermi level is in the band gap.

Fill Factor — the ratio of a photovoltaic cell's actual power to its power if both current and voltage were at their maximum. This is a key characteristic in evaluating cell performance.

Fixed Tilt Array — a photovoltaic (PV) array set in at a fixed angle with respect to horizontal.

Flat-Plate Array — a photovoltaic (PV) array that consists of non-concentrating PV modules.

Flat-Plate Collector — is a type of solar collector in which the absorber plate is enclosed in a flat, heat-insulated enclosure. The enclosure is closed off with a glass shield. Flat-plate collectors are usually not evacuated, thus allowing conductive and convective heat loss through the movement of air.

Flat-Plate Module — a collection of photovoltaic cells or material mounted on a rigid flat surface with the cells exposed freely to incoming sunlight.

Flat-Plate Photovoltaics (PV) — a photovoltaic (PV) array or module that consists of non-concentrating elements. Flat-plate arrays and modules use direct and diffuse sunlight. If the array is fixed in position, some portion of the direct sunlight is lost because of oblique sun-angles in relation to the array.

Float Charge — the voltage required to counteract the self-discharge of the battery at a certain temperature.

Float Life — the number of years that a battery can keep its stated capacity when it is kept at float charge.

Float Service — a battery process in which the battery is normally connected to an external current source.

Float-Zone Process — a method of growing a large-size, high-quality crystal whereby coils heat a polycrystalline ingot placed atop a single-crystal seed. As the coils are slowly raised the molten interface beneath the coils becomes single crystal.

Frequency — the number of repetitions per unit time of a complete waveform, expressed in Hertz (Hz).

Frequency Regulation — the variability in the output frequency. Some loads will switch off or not operate properly if frequency variations exceed 1%.

Fresnel Lens — an optical device that focuses light like a magnifying glass; concentric rings are faced at slightly different angles so that light falling on any ring is focused to the same point.

Full Sun — the amount of power density in sunlight received at the earth's surface at noon on a clear day (about 1,000 Watts/square meter).

G

Ga — chemical element symbol for Gallium

GaAs — chemical element symbol for Gallium Arsenide.

Gallium (Ga) — chemical element that is metallic in nature and used in making certain kinds of solar cells and semiconductor devices.

Gallium Arsenide (GaAs) — a crystalline, high-efficiency compound used to make certain types of solar cells and semiconductor material.

Gassing — the evolution of gas from one or more of the electrodes in the cells of a battery. Gassing commonly results from local action self-discharge or from the electrolysis of water in the electrolyte during charging.

Gassing Current — the portion of charge current that goes into electrolytical production of hydrogen and oxygen from the electrolytic liquid. This current increases with increasing voltage and temperature.

Gel-Type Battery — a lead-acid battery in which the electrolyte is composed of a silica gel matrix.

Gigawatt (GW) — a unit of power equal to 1 billion Watts; 1 million kilowatts, or 1,000 megawatts.

Grid — a large integrated system of electricity distribution from centralized locations to individual homes and businesses .

Grid-Connected System — a solar electric or photovoltaic (PV) system in which the PV array acts like a central generating plant, supplying power to the grid. It allows you to power your home or small business with renewable energy during those periods when the sun is plentiful. Excess electricity produced is fed back into the grid. When renewable resources are unavailable, electricity from the grid supplies your needs and eliminates the expense of electricity storage devices such as batteries.

Grid Coupling - Photovoltaic systems connected directly to the grid. Electricity not used domestically is fed into the grid (also called feeding the grid), but if electricity needs are not met by the photovoltaic system then current is provided by the grid.

Grid-Interactive System — same as grid-connected system.

Grid Lines — metallic contacts that are fused to the surface of the solar cell to provide a low resistance path for electrons to flow out to the cell interconnect wires.

H

Harmonic Content — the number of frequencies in the output waveform in addition to the primary frequency (50 or 60 Hz.). Energy in these harmonic frequencies is lost and may cause excessive heating of the load.

Hertz — a unit of frequency equal to one cycle per second. The term is used most frequently in connection with alternating electric currents, electromagnetic waves (light, radar, etc.), and sound.

Heterojunction — region of electrical contact between two different materials.

High Voltage Disconnect — the voltage at which a charge controller will disconnect the photovoltaic array from the batteries to prevent overcharging.

High Voltage Disconnect Hysteresis — the voltage difference between the high voltage disconnect set point and the voltage at which the full photovoltaic array current will be reapplied.

Hole — the vacancy where an electron would normally exist in a solid; behaves like a positively charged particle.

Homojunction — the region between an n-layer and a p-layer in a single material, photovoltaic cell.

Hybrid System — a solar electric or photovoltaic system that includes additional sources of electricity generation, such as wind or diesel generators.

Hydrogenated Amorphous Silicon — amorphous silicon with a small amount of incorporated hydrogen. The hydrogen neutralizes dangling bonds in the amorphous silicon, allowing charge carriers to flow more freely.

I

Incident Light — light that shines onto the face of a solar cell or module.

Indium Oxide — a wide band gap semiconductor that can be heavily doped with tin to make a highly conductive, transparent thin film. It is often used as a front contact or one component of a heterojunction solar cell.

Infrared Radiation — electromagnetic radiation whose wavelengths lie in the range from 0.75 micrometer to 1000 micrometers; invisible long wavelength radiation (heat) capable of producing a thermal or photovoltaic effect, though less effective than visible light.

Ingot — is a material that is cast into a shape suitable for further processing. Silicon ingots are used to manufacture mono-crystalline solar panels. The crystalline cells are uniformly constructed from slices of a large single crystal ingot. Silicon used in solar cell construction is refined to an almost 100% purity.

Input Voltage — a calculation determined by the total power required by the alternating current loads and the voltage of any direct current loads. Usually the larger the load, the higher the inverter input voltage. This keeps the current at levels where switches and other components are readily available.

Insolation — the solar power density incident on a surface of stated area and orientation, usually expressed as Watts per square meter or Btu per square foot per hour. See diffuse insolation and direct insolation.

Interconnect — a conductor within a module or other means of connection that provides an electrical interconnection between the solar cells.

Intrinsic Layer — a layer of semiconductor material, used in a photovoltaic device, whose properties are essentially those of the pure, undoped, material.

Intrinsic Semiconductor — an undoped semiconductor.

Inverter — a device that converts direct current electricity to alternating current either for stand-alone systems or to supply power to an electricity grid. Also known as a rectifier.

Ion — an electrically charged atom or group of atoms that has lost or gained electrons; a loss makes the resulting particle positively charged; a gain makes the particle negatively charged.

Irradiance — the direct, diffuse, and reflected solar radiation that strikes a surface. Usually expressed in kilowatts per square meter. Irradiance multiplied by time equals insolation.

ISPRA Guidelines — Guidelines for the Assessment of Photovoltaic Power Plants, published by the Joint Research Centre of the Commission of the European Communities, Ispra, Italy.

I-Type Semiconductor — semiconductor material that is left intrinsic, or undoped so that the concentration of charge carriers is characteristic of the material itself rather than of added impurities.

I-V Curve — graphical presentation of the current versus the voltage from a photovoltaic device as the load is increased from the short circuit (no load) condition to the open circuit (maximum voltage) condition. The shape of the curve characterizes cell performance.

J

Joule — a metric unit of energy or work; 1 joule per second equals 1 watt or 0.737 foot-pounds; 1 Btu equals 1,055 joules.

Junction — a region of transition between semiconductor layers, such as a p/n junction, which goes from a region that has a high concentration of acceptors (p-type) to one that has a high concentration of donors (n-type).

Junction Box — a photovoltaic (PV) generator junction box is an enclosure on the module where PV strings are electrically connected and where protection devices can be located, if necessary.

Junction Diode — a semiconductor device with a junction and a built-in potential that passes current better in one direction than the other. All solar cells are junction diodes.

K

Kilowatt (kW) — a standard unit of electrical power equal to 1000 watts, or to the energy consumption at a rate of 1000 joules per second.

Kilowatt-Hour (kWh) — 1,000 thousand watts acting over a period of 1 hour. The kWh is a unit of energy. 1 kWh=3600 kJ.

K-value — the heat transfer coefficient - the measured value of the heat flow which is transferred through an area of 1 m² at a temperature difference of 1 K. The units of measure are watts per square meter per temperature difference (W/m²K). K-value = energy / (area x temperature difference x time).

kWh — abbreviation for kilowatt-hour. 1 kWh = 1000 W over a time period of one hour. It is equivalent to 3.6 million Joules, or the amount of energy needed to increase the temperature of 100 litres of water by 10 °C.

kWp — abbreviation for kilowatt-peak, a measure of the peak output of a photovoltaic system

L

Langley (L) — a unit of solar irradiance. One gram calorie per square centimeter. 1 L = 85.93 kwh/m².

Lattice — the regular periodic arrangement of atoms or molecules in a crystal of semiconductor material.

Lead-Acid Battery — a general category that includes batteries with plates made of pure lead, lead-antimony, or lead-calcium immersed in an acid electrolyte.

Life — the period during which a system is capable of operating above a specified performance level.

Life-Cycle Cost — the estimated cost of owning and operating a photovoltaic system for the period of its useful life.

Light-Induced Defects — defects, such as dangling bonds, induced in an amorphous silicon semiconductor upon initial exposure to light.

Light Trapping — the trapping of light inside a semiconductor material by refracting and reflecting the light at critical angles; trapped light will travel further in the material. This greatly increases the probability of absorption and therefore of producing charge carriers.

Linear Concentrating Systems — uses lenses or mirrors and tracking systems to focus a large area of sunlight into a small beam. The concentrated heat is then used as a heat source for a conventional power plant. A wide range of concentrating technologies exists including the parabolic trough, the concentrating linear fresnel reflector, the Stirling dish and the solar power tower.

Line-Commutated Inverter — an inverter that is tied to a power grid or line. The commutation of power (conversion from direct current to alternating current) is controlled by the power line, so that, if there is a failure in the power grid, the photovoltaic system cannot feed power into the line.

Line Loss — Energy lost due to inherent inefficiencies in an electrical transmission and distribution system.

Liquid Electrolyte Battery — a battery containing a liquid solution of acid and water. Distilled water may be added to these batteries to replenish the electrolyte as necessary. Also called a flooded battery because the plates are covered with the electrolyte.

Line Focus System — a type of focus system used when very high temperatures are required from solar radiation. The line focus system has a trough-shaped parabolic dish or line of mirrors to concentrate the sun's light which is then converted into electricity.

Load — The demand on an energy producing system; the energy consumption or requirement of a piece or group of equipment. Usually expressed in terms of amperes or watts in reference to electricity.

Load Circuit — the wire, switches, fuses, etc. that connect the load to the power source.

Load Current (A) — the current required by the electrical device.

Load Resistance — the resistance presented by the load. See resistance.

Low Voltage Cutoff (LVC) — the voltage level at which a charge controller will disconnect the load from the battery.

Low Voltage Disconnect — the voltage at which a charge controller will disconnect the load from the batteries to prevent over-discharging.

Low Voltage Disconnect Hysteresis — the voltage difference between the low voltage disconnect set point and the voltage at which the load will be reconnected.

Low Voltage Warning — a warning buzzer or light that indicates the low battery voltage set point has been reached.

M

Maintenance-Free Battery — a sealed battery to which water cannot be added to maintain electrolyte level.

Majority Carrier — current carriers (either free electrons or holes) that are in excess in a specific layer of a semiconductor material (electrons in the n-layer, holes in the p-layer) of a cell.

Maximum Power Point (MPP) — the point on the current-voltage (I-V) curve of a module under illumination, where the product of current and voltage is maximum. For a typical silicon cell, this is at about 0.45 volts.

Maximum Power Point Tracker (MPPT) — means of a power conditioning unit that automatically operates the photovoltaic generator at its maximum power point under all conditions.

Maximum Power Tracking — operating a photovoltaic array at the peak power point of the array's I-V curve where maximum power is obtained. Also called peak power tracking.

Megawatt (MW) — 1,000 kilowatts, or 1 million watts; standard measure of electric power plant generating capacity.

Megawatt-Hour — 1,000 kilowatt-hours or 1 million watt-hours.

Microgroove — a small groove scribed into the surface of a solar cell, which is filled with metal for contacts.

Minority Carrier — a current carrier, either an electron or a hole, that is in the minority in a specific layer of a semiconductor material; the diffusion of minority carriers under the action of the cell junction voltage is the current in a photovoltaic device.

Minority Carrier Lifetime — the average time a minority carrier exists before recombination.

Modified Sine Wave — a waveform that has at least three states (i.e., positive, off, and negative). It has less harmonic content than a square wave.

Modularity — the use of multiple inverters connected in parallel to service different loads.

Module — several individual solar cells connected together in an environmentally protected housing producing a standard output voltage and power. Multiple modules/panels can be assembled into an array for increased power and/or voltage. Same as photovoltaic (PV) module.

Module Derate Factor — a factor that lowers the photovoltaic module current to account for field operating conditions such as dirt accumulation on the module.

Monocrystalline Silicon Cells — a material used in solar cells that are saw-cut from a single cylindrical silicon crystal boule. They are then cut into slices of .2 to .4 mm thick discs or wafers and processed into individual solar cells.

Monolithic — fabricated as a single structure.

Movistor — Metal Oxide Varistor - used to protect electronic circuits from surge currents such as those produced by lightning.

Multicrystalline — a semiconductor (photovoltaic) material composed of variously oriented, small, individual silicon crystals. Also referred to as polycrystalline or semicrystalline.

Multijunction Device — a high-efficiency photovoltaic device containing two or more cell junctions, each of which is optimized for a particular part of the solar spectrum.

Multi-Stage Controller — a charging controller unit that allows different charging currents as the battery nears full state of charge.

N

National Electrical Code (NEC) — contains guidelines for all types of electrical installations. The 1984 and later editions of the NEC contain Article 690, "Solar Photovoltaic Systems" which should be followed when installing a PV system.

National Electrical Manufacturers Association (NEMA) — the organization sets standards for some non-electronic products like junction boxes.

NEC — abbreviation for National Electrical Code.

NEMA — abbreviation for National Electrical Manufacturers Association.

Net Metering — an arrangement with your local power company where the excess electricity generated by grid-connected renewable energy systems rolls back your electricity meter as it is fed back into the grid. If you use more electricity than your system feeds into the grid during a month, you will pay your power provider only for the difference between what you used and what you produced. Any net energy produced is sold back to the power company.

Nickel Cadmium Battery — a battery containing nickel and cadmium plates and an alkaline electrolyte.

Nominal Voltage — a reference voltage used to describe batteries, modules, or systems (i.e., a 12-volt or 24-volt battery, module, or system).

Non Focus System — are the most familiar of the focus systems and are generally what one commonly assumes when they think of solar collectors. The main solar thermal panels and solar cell panels installed in homes across the country use the non-focus system. The advantage of using the non-focus system is that it can diffuse the sunlight without needing any further adaptation.

Normal Operating Cell Temperature (NOCT) — the estimated temperature of a photovoltaic module when operating under 800 w/m² irradiance, 20°C ambient temperature and wind speed of 1 meter per second. NOCT is used to estimate the nominal operating temperature of a module in its working environment.

N-dopant — a chemical element (or impurity) added in small amounts to an otherwise pure semiconductor material to modify the electrical properties of the material. An n-dopant introduces more electrons.

N-Type — a negative semiconductor material in which there are more electrons than holes; current is carried through it by the flow of electrons.

N-Type Semiconductor — a semiconductor produced by doping an intrinsic semiconductor with an electron-donor impurity (e.g., phosphorus in silicon).

N-Type Silicon — a silicon material that has been doped with a material that has more electrons in its atomic structure than does silicon.

O

Off-Grid System — a system that uses battery banks to store energy for the times a renewable source isn't available

Ohm — a measure of the electrical resistance of a material equal to the resistance of a circuit in which the potential difference of 1 volt produces a current of 1 ampere.

Ohm's Law — the various formulas that define the relationship between resistance(R), voltage(E), and current(I) as in $E=I \cdot R$, $I=E/R$, $R=E/I$.

One-Axis Tracking — a solar tracking system that moves in only one direction or axis generally following the sun in its arc across the sky from east to west.

Open-Circuit Voltage (Voc) — the maximum possible voltage across a photovoltaic cell; the voltage across the cell in sunlight when no current is flowing.

Open Loop System — a type of hot-water solar heating that uses a direct pumped system with one or more solar energy collectors installed on the roof and a storage tank below in a garage or utility room. A pump circulates the water from the tank back and forth to the collector. A differential controller senses the temperature variation between water leaving the solar collector and the coldest water in the storage tank. When the water in the solar collector is warmer than the water in the tank, the controller turns the pump on. The pump turns off when the water temperature drops to about 3–5 degrees.

Operating Point — the current and voltage that a photovoltaic module or array produces when connected to a load. The operating point is dependent on the load or the batteries connected to the output terminals of the array.

Orientation — placement with respect to the cardinal directions, N, S, E, W; azimuth is the measure of orientation from north.

Outgas — the same as gassing.

Overcharge — forcing current into a fully charged battery. The battery will be damaged if overcharged for a long period.

P

Packing Factor — the ratio of array area to actual land area or building envelope area for a system; or, the ratio of total solar cell area to the total module area, for a module.

Panel — same as photovoltaic (PV) panel.

Parabolic Mirror/Trough — concentrate the direct solar radiation on the absorber, which is placed at the center of the mirror, and therefore can reach very high temperatures. Most diffuse radiation cannot be concentrated in this way.

Parallel Connection — a means of joining solar cells or photovoltaic modules by connecting positive leads together and negative leads together; this type of configuration increases the current, but not the voltage.

Passive Solar — harnesses the sun's energy without the use of mechanical devices.

Passivation — a chemical reaction that eliminates the detrimental effect of electrically reactive atoms on a solar cell's surface.

P-dopant — a chemical element (or impurity) added in small amounts to an otherwise pure semiconductor material to modify the electrical properties of the material. A p-dopant creates electron holes or vacancies.

Peak Demand/Load — the maximum energy demand or load in a specified time period.

Peak Power Current — amperes produced by a photovoltaic module or array operating at the voltage of the I-V curve that will produce maximum power from the module.

Peak Power Point — the operating point of the I-V (current-voltage) curve for a solar cell or photovoltaic module where the product of the current value times the voltage value is a maximum.

Peak Power Tracking — see maximum power tracking.

Peak Sun Hours — the equivalent number of hours per day when solar irradiance averages 1,000 w/m². For example, six peak sun hours means that the energy received during total daylight hours equals the energy that would have been received had the irradiance for six hours been 1,000 w/m².

Peak Watt — a unit used to rate the performance of solar cells, modules, or arrays; the maximum nominal output of a photovoltaic device, in watts (Wp) under standardized test conditions, usually 1,000 watts per square meter of sunlight with other conditions, such as temperature specified.

Phantom Load — the small power used by an appliance even when it is turned off. Examples of phantom loads include appliances with electronic clocks or timers and devices with remote controls whose circuits remain active in order to detect the remote control signal to power up.

Phosphorous (P) — a chemical element used as a dopant in making n-type semiconductor layers.

Photocurrent — an electric current induced by radiant energy.

Photoelectric Cell — a device for measuring light intensity that works by converting light falling on, or reach it, to electricity, and then measuring the current; used in photometers.

Photoelectrochemical Cell — a type of photovoltaic device in which the electricity induced in the cell is used immediately within the cell to produce a chemical, such as hydrogen, which can then be withdrawn for use.

Photon — a particle of light that acts as an individual unit of energy.

Photovoltaic(s) (PV) — the direct conversion of light into electricity.

Photovoltaic (PV) Array — an interconnected system of PV modules that function as a single electricity-producing unit. The modules are assembled as a discrete structure, with common support or mounting. In smaller systems, an array can consist of a single module.

Photovoltaic (PV) Cell — the smallest semiconductor element within a PV module to perform the immediate conversion of light into electrical energy (direct current voltage and current). Also called a solar cell.

Photovoltaic (PV) Conversion Efficiency — the ratio of the electric power produced by a photovoltaic device to the power of the sunlight incident on the device.

Photovoltaic (PV) Device — a solid-state electrical device that converts light directly into direct current electricity of voltage-current characteristics that are a function of the characteristics of the light source and the materials in and design of the device. Solar photovoltaic devices are made of a range of semiconductor materials including silicon, cadmium sulfide, cadmium telluride, and gallium arsenide, and in single crystalline, multicrystalline, or amorphous forms.

Photovoltaic (PV) Effect — the phenomenon that occurs when photons, the "particles" in a beam of light, knock electrons loose from the atoms they strike. When this property of light is combined with the properties of semiconductors, electrons flow in one direction across a junction, setting up a voltage. With the addition of circuitry, current will flow and electric power will be available.

Photovoltaic (PV) Generator — the total of all PV strings of a PV power supply system, which are electrically interconnected.

Photovoltaic (PV) Module — the smallest environmentally protected, essentially planar assembly of solar cells and ancillary parts, such as interconnections, terminals, [and protective devices such as diodes] intended to generate direct current power under unconcentrated sunlight. The structural (load carrying) member of a module can either be the top layer (superstrate) or the back layer (substrate).

Photovoltaic (PV) Panel — often used interchangeably with PV module (especially in one-module systems), but more accurately used to refer to a physically connected collection of modules (i.e., a laminate string of modules used to achieve a required voltage and current).

Photovoltaic (PV) System — a complete set of components for converting sunlight into electricity by the photovoltaic process, including the array and balance of system components.

Photovoltaic-Thermal (PV/T) System — a photovoltaic system that, in addition to converting sunlight into electricity, collects the residual heat energy and delivers both heat and electricity in usable form. Also called a total energy system.

Physical Vapor Deposition — a method of depositing thin semiconductor photovoltaic films. With this method, physical processes, such as thermal evaporation or bombardment of ions, are used to deposit elemental semiconductor material on a substrate.

P-I-N — a semiconductor photovoltaic (PV) device structure that layers an intrinsic semiconductor between a p-type semiconductor and an n-type semiconductor; this structure is most often used with amorphous silicon PV devices.

Plates — a metal plate, usually lead or lead compound, that is immersed in the electrolyte in a battery.

P/N — a semiconductor photovoltaic device structure in which the junction is formed between a p-type layer and an n-type layer.

Pocket Plate — a plate for a battery in which active materials are held in a perforated metal pocket.

Point-Contact Cell — a high efficiency silicon photovoltaic concentrator cell that employs light trapping techniques and point-diffused contacts on the rear surface for current collection.

Point focus — a saucer-shaped, or parabolic, dish that is used to focus diffuse sunlight into a concentrated point of solar radiation. It could be combined with heliostat to concentrate light at a point or focus. A high-concentration of photovoltaic cells or a thermal energy 'receiver', such as those used in Stirling Engines can be positioned at the focus point.

Polycrystalline Silicon — a material used to make photovoltaic cells, which consist of many, randomly-oriented individual crystals. Sometimes referred to as semicrystalline or multicrystalline.

Power Conditioning — the process of modifying the characteristics of electrical power (for e.g., inverting direct current to alternating current).

Power Conditioning Equipment — electrical equipment, or power electronics, that are used to convert power from a photovoltaic array into a form suitable for subsequent use. A collective term for inverter, converter, battery charge regulator, and blocking diode.

Power Conversion Efficiency — The ratio of output power to input power of the inverter.

Power Density — The ratio of the power available from a battery to its mass (W/kg) or volume (W/l).

Power Factor (PF) — the ratio of actual power being used in a circuit, expressed in watts or kilowatts, to the power that is apparently being drawn from a power source, expressed in volt-amperes or kilovolt-amperes.

Primary Battery — a battery whose initial capacity cannot be restored by charging.

Projected Area — the net south-facing glazing area projected on a vertical plane.

P-Type Semiconductor — A semiconductor in which holes carry the current; produced by doping an intrinsic semiconductor with an electron acceptor impurity (e.g., boron in silicon).

Pulse-Width-Modulated (PWM) Wave Inverter — A type of power inverter that produce a high quality (nearly sinusoidal) voltage, at minimum current harmonics.

PV — the abbreviation for photovoltaics.

PV Array - a group of solar photovoltaic modules connected together to increase voltage and/or power to the level required for a given system.

PV Module – a number of individual solar cells connected together in an environmentally-protected housing that produces a standard output voltage and power. Multiple modules and panels can be assembled into an array for increased power and/or voltage

Pyranometer — an instrument used for measuring global solar irradiance.

Pyrheliometer — an instrument used for measuring direct beam solar irradiance. Uses an aperture of 5.7° to transcribe the solar disc.

Q

Quad — one quadrillion Btu (1,000,000,000,000,000 Btu).

Qualification Test — a formula applied to a selected set of photovoltaic modules involving the application of defined electrical, mechanical, or thermal stress in a prescribed manner and amount. Test results are subject to a list of defined requirements.

R

Rated Battery Capacity — term used by battery manufacturers to indicate the maximum amount of energy that can be withdrawn from a battery under specified discharge rate and temperature.

Rated Module Current (A) — the current output of a photovoltaic module measured at standard test conditions of 1,000 w/m² and 25°C cell temperature.

Rated Power — rated power delivery of the inverter under ideal circumstances labeled as “standard test conditions”.

Reactive Power — the sine of the phase angle between the current and voltage waveforms in an alternating current system. See power factor.

Recombination — the action of a free electron falling back into a hole. Recombination processes are either radiative, where the energy of recombination results in the emission of a photon, or nonradiative, where the energy of recombination is given to a second electron which then relaxes back to its original energy by emitting phonons. Recombination can take place in the bulk of the semiconductor, at the surfaces, in the junction region, at defects, or between interfaces.

Rectifier — a device that converts alternating current to direct current. Also known as an inverter.

Regulator — a device prevents overcharging of batteries by controlling charge cycle-usually adjustable to conform to specific battery needs.

Remote Systems — an autonomous or hybrid photovoltaic system not connected to a grid. Also known as a stand-alone system, it may or may not have storage. Most remote systems require batteries or some other form of storage.

Renewable Energy — energy from sources that are not easily exhausted such as moving water (hydro, tidal and wave power), biomass, geothermal energy, solar energy, wind energy, and energy from solid waste treatment plants.

Reserve Capacity — the amount of generating capacity a central power system must maintain to meet peak loads.

Resistance (R) — the property of a conductor, which opposes the flow of an electric current resulting in the generation of heat in the conducting material. The measure of the resistance of a given conductor is the electromotive force needed for a unit current flow. The unit of resistance is ohms.

Resistive Voltage Drop — the voltage developed across a cell by the current flow through the resistance of the cell.

Reverse Current Protection — any method of preventing unwanted current flow from the battery to the photovoltaic array (usually at night). See blocking diode.

Ribbon (Photovoltaic) Cells — a type of photovoltaic device made in a continuous process of pulling material from a molten bath of photovoltaic material, such as silicon, to form a thin sheet of material.

RMS — abbreviation for Root Mean Square

Root Mean Square (RMS) — The square root of the average square of the instantaneous values of an ac output. For a sine wave the RMS value is 0.707 times the peak value. The equivalent value of alternating current, I , that will produce the same heating in a conductor with resistance, R , as a dc current of value I .

S

Sacrificial Anode — a piece of metal buried near a structure that is to be protected from corrosion. The metal of the sacrificial anode is intended to corrode and reduce the corrosion of the protected structure.

Satellite Power System (SPS) — a concept for providing large amounts of electricity for use on the Earth from one or more satellites in geosynchronous earth orbit. A very large array of solar cells on each satellite would provide electricity, which would be converted to microwave energy and beamed to a receiving antenna on the ground. There, it would be reconverted into electricity and distributed the same as any other centrally generated power, through a grid.

Schottky Barrier — a cell barrier established as the interface between a semiconductor, such as silicon, and a sheet of metal.

Scribing — the cutting of a grid pattern of grooves in a semiconductor material, generally for the purpose of making interconnections.

Sealed Battery — a battery with a captive electrolyte and a resealing vent cap, also called a valve-regulated battery. Electrolyte cannot be added to this battery.

Seasonal Depth of Discharge — an adjustment factor used in some system sizing procedures which "allows" the battery to be gradually discharged over a 30-90 day period of poor solar insolation. This factor results in a slightly smaller photovoltaic array.

Secondary Battery — a battery that can be recharged.

Selective Coatings — a coating applied to an absorber to enhance absorption and transform a large part of the short-wave solar radiation into heat. It also significantly reduces the emission of the long-wave heat radiation from the absorber. The established selective coatings are black chrome and black nickel, produced by galvanic processes, achieve maximum absorptivity rates between 88 and 96 % and emissivity rates around 10 to 15 %.

Self-Discharge — the rate at which a battery, without a load, will lose its charge.

Semiconductor — any material that has a limited capacity for conducting an electric current. Some semiconductors, including silicon, gallium arsenide, copper indium diselenide, and cadmium telluride, are uniquely suited to the photovoltaic conversion process.

Semicrystalline — another name for multicrystalline silicon.

Series Connection — a method of joining photovoltaic cells by connecting positive leads to negative leads; such a configuration increases the voltage.

Series Controller — a charge controller that interrupts the charging current by open-circuiting the photovoltaic (PV) array. The control element is in series with the PV array and battery.

Series Regulator — a type of battery charge regulator where the charging current is controlled by a switch connected in series with the photovoltaic module or array.

Series Resistance — Parasitic resistance to current flow in a cell due to mechanisms such as resistance from the bulk of the semiconductor material, metallic contacts, and interconnections.

Shallow-Cycle Battery — a battery with small plates that cannot withstand many discharges to a low state-of-charge.

Shelf Life of Batteries — the length of time, under specified conditions, that a battery can be stored so that it keeps its guaranteed capacity.

Short-Circuit Current (I_{sc}) — the current flowing freely through an external circuit that has no load or resistance; the maximum current possible.

Shunt Controller — a charge controller that redirects or shunts the charging current away from the battery. The controller requires a large heat sink to dissipate the current from the short-circuited photovoltaic array. Most shunt controllers are for smaller systems producing 30 amperes or less.

Shunt Regulator — type of a battery charge regulator where the charging current is controlled by a switch connected in parallel with the photovoltaic (PV) generator. Shorting the PV generator prevents overcharging of the battery.

Siemens Process — a commercial method of making purified silicon.

Silicon (Si) — a semi-metallic chemical element that makes a superb semiconductor material for photovoltaic devices. It crystallizes in face-centered cubic lattice like a diamond. It's commonly found in sand and quartz (as the oxide).

Sine Wave — a waveform corresponding to a single-frequency periodic oscillation that can be mathematically represented as a function of amplitude versus angle in which the value of the curve at any point is equal to the sine of that angle.

Sine Wave Inverter — an inverter that produces utility-quality, sine wave power forms.

Single-Crystal Material — a material that is composed of a single crystal or a few large crystals.

Single-Crystal Silicon — a material with a single crystalline formation. Many photovoltaic cells are made from single-crystal silicon.

Single-Stage Controller — a charge controller that redirects all charging current as the battery nears full state-of-charge.

Sizing — The process of designing a solar electric system to meet the required operating loads based on the total wattage of all appliances in the system.

Solar Cell — a photovoltaic [PV] cell

Solar Collector — any of several devices that absorb and accumulate solar radiation for use as a source of energy for the heating of water or buildings or the production of electricity. See Solar Thermal Collector also.

Solar Constant — the average amount of solar radiation that reaches the earth's upper atmosphere on a surface perpendicular to the sun's rays; equal to 1353 Watts per square meter or 492 Btu per square foot.

Solar Cooling — the use of solar thermal energy or solar electricity to power a cooling appliance. Photovoltaic systems can power evaporative coolers, heat pumps and air conditioners.

Solar Oven — a device that uses sunlight as its energy source to cook food. They use no fuel and cost nothing to run. An insulated enclosure with a glazed surface that reaches 300 to 400 degrees F. in full sun and is used for cooking. There are a variety of types of solar cookers with over 65 major designs and hundreds of variations.

Solar Energy — the electromagnetic energy transmitted from the sun (solar radiation). The amount that reaches the earth is equal to one billionth of total solar energy generated, or the equivalent of about 420 trillion kilowatt-hours.

Solar-Grade Silicon — intermediate-grade silicon used in the manufacture of solar cells. It is less expensive than electronic-grade silicon.

Solar Insolation — same as insolation

Solar Irradiance — See same as irradiance.

Solar Noon — the time of the day, at a specific location, when the sun reaches its highest, apparent point in the sky; equal to true or due, geographic south.

Solar Panel — a solar photovoltaic [PV] panel

Solar Resource — the quantity of solar insolation a site receives, usually measured in kWh/m²/day, which is equivalent to the number of peak sun hours.

Solar Spectrum — the total distribution of electromagnetic radiation emanating from the sun. The different regions of the solar spectrum are described by their wavelength range. The visible region extends from about 390 to 780 nanometers (a nanometer is one billionth of one meter). About 99 percent of solar radiation is contained in a wavelength region from 300 nm (ultraviolet) to 3,000 nm (near-infrared). The combined radiation in the wavelength region from 280 nm to 4,000 nm is called the broadband, or total, solar radiation.

Solar Electric Systems — Solar energy conversion technologies that convert solar energy to electricity, by heating a working fluid to power a turbine that drives a generator. Examples of these systems include central receiver systems, parabolic dish, and solar trough.

Solar Thermal Collector — is a solar collector specifically intended to extract the energy of the sun directly into a more usable or storable form. It is usually used to denote more complex solar installations including solar parabolic, solar trough and solar towers. The term is also applied to simple solar hot water panels.

Solar Tiles — roof shingles powered by solar energy. Some can be placed right onto the roof just like normal shingles while others can actually be interspersed with regular asphalt shingles. There are two types of solar tiles: paneled shingles and single shingles. Paneled shingles are similar to a normal strip of shingles and make up for a number of individual shingles. This type of solar roof tile is made up of a varying number of silicon solar cells. They are flexible and actually feel like regular shingles. The second type of solar roof tile is a single shingle, they resemble cedar or clay shingles in terms of size and. These are clearly more work intensive to install and even more pricey than the other variety.

Solar Water Heater — water heated by the use of solar energy. Solar water heating systems are generally composed of solar thermal collectors, a water storage tank or another point of usage, interconnecting pipes and a fluid system that moves the heat from the collector to the tank.

Space Charge — same as depletion zone

Specific Gravity — the ratio of the weight of the solution to the weight of an equal volume of water at a specified temperature. Used as an indicator of battery state-of-charge.

Spinning Reserve — electric power plant or utility capacity on-line and running at low power in excess of actual load.

Split-Spectrum Cell — a compound photovoltaic device in which sunlight is first divided into spectral regions by optical means. Each region is then directed to a different photovoltaic cell optimized for converting that portion of the spectrum into electricity. Such a device achieves significantly greater overall conversion of incident sunlight into electricity. See multijunction device.

Sputtering — a process used to apply photovoltaic semiconductor material to a substrate by a physical vapor deposition process where high-energy ions are used to bombard elemental sources of semiconductor material, which eject vapors of atoms that are then deposited in thin layers on a substrate.

Square Wave — a waveform that has only two states, (i.e., positive or negative). A square wave contains a large number of harmonics.

Square Wave Inverter — a type of inverter that produces square wave output. It consists of a direct current source, four switches, and the load. The switches are power semiconductors that can carry a large current and withstand a high voltage rating. The switches are turned on and off at a correct sequence, at a certain frequency.

Staebler-Wronski Effect — the tendency of the sunlight to electricity conversion efficiency of amorphous silicon photovoltaic devices to degrade or drop with the initial exposure to light.

Stand-Alone System — an autonomous or hybrid photovoltaic system not connected to a grid. May or may not have storage, but most stand-alone systems require batteries or some other form of storage.

Stand-Off Mounting — a technique for mounting a photovoltaic array on a sloped roof, which involves mounting the modules a short distance above the pitched roof and tilting them to the optimum angle.

Standard Reporting Conditions (SRC) — a fixed set of conditions (including meteorological) to which the electrical performance data of a photovoltaic module are translated from the set of actual test conditions.

Standard Test Conditions (STC) — conditions under which a module is typically tested in a laboratory.

Standby Current —the amount of current used by the inverter when no load is active. The efficiency of the inverter is lowest when the load demand is low.

Starved Electrolyte Cell — a type of battery containing little or no free fluid electrolyte.

State-of-Charge (SOC) — the available capacity remaining in the battery, expressed as a percentage of the rated capacity.

Stirling Motor/Engine - a heat engine that operates by cyclic compression and expansion of air or other gas, the working fluid, at different temperature levels such that there is a net conversion of heat energy to mechanical work. When placed at the focus of a parabolic mirror a Stirling engine can convert solar energy to electricity with an efficiency better than non-concentrated photovoltaic cells, and comparable to concentrated photovoltaics.

Storage Battery — a device capable of transforming energy from electric to chemical form and vice versa. The reactions are almost completely reversible. During discharge, chemical energy is converted to electric energy and is consumed in an external circuit or apparatus.

Stratification — a condition that occurs when the acid concentration varies from top to bottom in the battery electrolyte. Periodic, controlled charging at voltages that produce gassing will mix the electrolyte.

String — a number of photovoltaic modules or panels interconnected electrically in series to produce the operating voltage required by the load.

Substrate — the physical material upon which a photovoltaic cell is applied. Substrates for the manufacture of solar cells are glass, metal foil, wafer and plastic film.

Subsystem — any one of several components in a photovoltaic system (for example -- array, controller, batteries, inverter, load).

Sulfation — a condition that afflicts unused and discharged batteries; large crystals of lead sulfate grow on the plate, instead of the usual tiny crystals, which makes the battery extremely difficult to recharge.

Superconducting Magnetic Energy Storage (SMES) — SMES technology uses the superconducting characteristics of low-temperature materials to produce intense magnetic fields to store energy. It has been proposed as a storage option to support large-scale use of photovoltaics as a means to smooth out fluctuations in power generation.

Superconductivity — the abrupt and large increase in electrical conductivity exhibited by some metals as the temperature approaches absolute zero.

Superstrate — the covering on the sunny side of a photovoltaic (PV) module, providing protection for the PV materials from impact and environmental degradation while allowing maximum transmission of the appropriate wavelengths of the solar spectrum.

Surge Capacity — the maximum power, usually 3-5 times the rated power, that can be provided over a short time.

System Availability — the percentage of time (usually expressed in hours per year) when a photovoltaic system will be able to fully meet the load demand.

System Operating Voltage — the photovoltaic array output voltage under load. The system operating voltage is dependent on the load or batteries connected to the output terminals.

System Storage — a means of saving available solar energy when it is available and stored for a time when it can be used. Off-grid photovoltaic systems have traditionally used rechargeable batteries to store excess electricity. Grid-tied systems can send excess electricity to the transmission grid.

T

Tare Loss — the loss caused by a charge controller. One minus tare loss, expressed as a percentage, is equal to the controller efficiency.

Temperature Compensation — A circuit that adjusts the charge controller activation points depending on battery temperature. This feature is recommended if the battery temperature is expected to vary more than $\pm 5^{\circ}\text{C}$ from ambient temperature.

Temperature Factors — It is common for three elements in photovoltaic system sizing to have distinct temperature corrections: a factor used to decrease battery capacity at cold temperatures; a factor used to decrease PV module voltage at high temperatures; and a factor used to decrease the current carrying capability of wire at high temperatures.

Thermal Storage -- four primary ways to store solar thermal energy are (1) sensible-heat-storage systems, which store thermal energy in materials with good heat-retention qualities; (2) latent-heat-storage systems, which store solar thermal energy in the latent heat of fusion or vaporization of certain materials undergoing a change of phase; (3) chemical energy storage, which uses reversible reactions (for example, the dissociation-association reaction of sulfuric acid and water); and (4) electrical or mechanical storage, particularly through the use of storage batteries (electrical) or compressed air (mechanical).

Thermophotovoltaic Cell (TPV) — a device where sunlight concentrated onto a absorber heats it to a high temperature, and the thermal radiation emitted by the absorber is used as the energy source for a photovoltaic cell that is designed to maximize conversion efficiency at the wavelength of the thermal radiation.

Thermo-Siphon System — a method of passive heat exchange based on natural convection that circulates liquid without the requirement of a mechanical pump. This circulation can either be open-loop or it can be a vertical closed-loop circuit.

Thick-Crystalline Materials — semiconductor material, typically measuring from 200-400 microns thick, that is cut from ingots or ribbons.

Thick-film Silicon — a type of multicrystalline technology where the silicon is deposited in a continuous process onto a base material giving a fine grained, sparkling appearance. It is created by drawing flat thin films from the molten silicon and results in a multicrystalline structure.

Thin Film — a layer of semiconductor material, such as copper indium diselenide or gallium arsenide, a few microns or less in thickness, used to make photovoltaic cells.

Thin Film Photovoltaic Module — a type of photovoltaic module constructed with sequential layers of thin film semiconductor materials.

Tilt Angle — the angle at which a photovoltaic array is set to face the sun relative to a horizontal position. The tilt angle can be set or adjusted to maximize seasonal or annual energy collection.

Tin Oxide — a wide band-gap semiconductor similar to indium oxide; used in heterojunction solar cells or to make a transparent conductive film, called NESA glass when deposited on glass.

Total AC Load Demand — the total of the alternating current loads. This value is important when selecting an inverter.

Total Harmonic Distortion — the measure of closeness in shape between a waveform and it's fundamental component.

Total Internal Reflection — the trapping of light by refraction and reflection at critical angles inside a semiconductor device so that it cannot escape the device and must be eventually absorbed by the semiconductor.

Tracking Array — a photovoltaic (PV) array that follows the path of the sun to maximize the solar radiation incident on the PV surface. The two most common orientations are (1) one axis where the array tracks the sun east to west and (2) two-axis tracking where the array points directly at the sun at all times. Tracking arrays use both the direct and diffuse sunlight. Two-axis tracking arrays capture the maximum possible daily energy.

Transformer — An electromagnetic device that changes the voltage of alternating current electricity.

Tray Cable (TC) — may be used for interconnecting balance-of-systems.

Trickle Charge — a charge at a low rate, balancing through self-discharge losses, to maintain a cell or battery in a fully-charged condition.

Two-Axis Tracking — A photovoltaic array tracking system capable of rotating independently about two axes (e.g., vertical and horizontal).

Tunneling — Quantum mechanical concept whereby an electron is found on the opposite side of an insulating barrier without having passed through or around the barrier.

U

Ultraviolet — electromagnetic radiation in the wavelength range of 4 to 400 nanometers.

Underground Feeder (UF) — may be used for photovoltaic array wiring if sunlight resistant coating is specified; can also be used for interconnecting balance-of-system components but not recommended for use within battery enclosures.

Underground Service Entrance (USE) — used within battery enclosures and for interconnecting balance-of-systems.

Uninterruptible Power Supply (UPS) — the designation of a power supply providing continuous uninterruptible service. The UPS units contain batteries.

Utility-Interactive Inverter — an inverter that can operate only when tied to the utility grid. It uses the existing line-voltage frequency on the utility line as a control parameter to guarantee that the photovoltaic system's output is fully synchronized with the utility power.

V

Vacuum Evaporation - the process of depositing thin films of semiconductor material by the evaporation of elemental sources in a vacuum.

Vacuum Zero — the energy of an electron at rest in empty space; used as a reference level in energy band diagrams.

Valence Band — the highest energy band in a semiconductor that can be filled with electrons.

Valence Level Energy/Valence State — energy content of an electron in orbit about an atomic nucleus. Also called bound state.

Varistor — a voltage-dependent variable resistor. It is usually used to protect sensitive equipment from power spikes or lightning strikes by shunting the energy to ground.

Vented Cell — a type of battery designed with a vent mechanism to expel gases generated during charging.

Vertical Multijunction (VMJ) Cell — a compound cell made of different semiconductor materials in layers, one above the other. Sunlight entering the top passes through successive cell barriers, each of which converts a separate portion of the spectrum into electricity, thus achieving greater total conversion efficiency of the incident light. Also called a multiple junction cell. See multijunction device and split-spectrum cell.

Volt (V) — a unit of electrical force equal to that amount of electromotive force that will cause a steady current of one ampere to flow through a resistance of one ohm.

Voltage — the amount of electromotive force, measured in volts, that exists between two points.

Voltage at Maximum Power (Vmp) — the voltage at which maximum power is available from a photovoltaic module.

Voltage Protection —sensing circuits on inverters that will disconnect the unit from the battery if input voltage limits are exceeded.

Voltage Regulation — This indicates the variability in the output voltage. Some loads will not tolerate voltage variations greater than a few percent.

W

Wafer — a thin sheet of semiconductor (photovoltaic material) made by cutting it from a single crystal or ingot.

Watt — the rate of energy transfer equivalent to one ampere under an electrical pressure of one volt. One watt equals 1/746 horsepower, or one joule per second. It is the product of voltage and current (amperage).

Watt-Hour — 1 watt produced or consumed for a period of 1 hour

Wattmeter — a device for measuring power production or usage displayed in watts

Waveform — the shape of the phase power at a certain frequency and amplitude.

Wet Shelf Life — the period of time that a charged battery, when filled with electrolyte, can remain unused before dropping below a specified level of performance.

Window — a wide band gap material chosen for its transparency to light. Generally used as the top layer of a photovoltaic device, the window allows almost all of the light to reach the semiconductor layers beneath.

Work Function — the energy difference between the Fermi level and vacuum zero. The minimum amount of energy it takes to remove an electron from a substance into the vacuum.

Z

Zenith Angle — the angle between the direction of interest (of the sun, for example) and the zenith (directly overhead).

PLEASE NOTE: We have worked to make this Solar Power Dictionary as complete as possible. Think we missed something? Think we got something wrong? Please do contact us and help us to make this dictionary more complete and up-to-date.